

Aircraft Tyre Inflators

Info / Accessories



Designed for high pressure aircraft tyres, these robust yet lightweight units are available with a calibration of 45 - 300 lbf/in², and offer guaranteed accuracy.

The magnified linear scale is easy to read, whilst the attractive slim line design with ergonomic "2 click action" trigger makes them comfortable and easy to use. The Aircraft Model comes complete with "Skydrol" corrosion resistant hose.

PCL's high pressure inflators are designed to be durable, with an aluminium body and impact absorbing rubber bumper. Made for inflation only, they do not come with a calibration certificate.

Key Product Benefits

- Reduced operating costs with fast inflation and deflation rates
- **Long life** - excellent shock resistance with robust durable design and construction
- **High versatility** - suitable for indoor and outdoor environments
- **Guaranteed accuracy** - individual testing
- Easy fitting and usage.

Key Product Features

- "Skydrol" corrosion resistant hose
- Cast aluminium body
- Proven linear spring gauge
- Proven linear gauge display
- Individual testing
- psi version and large range of options and accessories
- Inflation pressure up to 300psi.

Specifications

Reading Accuracy: 5psi

Max Inlet Pressure: 362psi

Inflation flow: 500l/min @ 13bar supply

Product Options

Part No.	Description	Hose Length	Tyre Valve Connection	Calibration
ALG5A01	Aircraft Model - body only	No Hose	No Connector	45-300lbf/in ²

ALG5A02	Aircraft Model	2m	8v1 screw-on	45-300lbf/in ²
ALG5A03	Aircraft Model	2m	12v1 screw-on	45-300lbf/in ²