

25 / 10 TON **SUPER DUTY**2 STAGE AIR / HYDRAULIC AXLE JACK



Model 546SD

- SUPER HEAVY DUTY, 2 Stage 50 Ton and 25 Ton built tough for the rigors of the Heavy Duty Trucking, Agricultural and Fleet business
- The piston head seal design is borrowed from Industrial technology providing a superior low and high pressure seal, giving this jack a much better hold under severe load conditions
- The extra long 138cm (54") handle can be locked in 3 positions for easy positioning of this jack in hard to reach places.
- An integral Descent Metering Valve maintains a controlled and safe lowering of the load
- Single piece base construction provides superior strength for increased load stability
- Double polished chromed pistons allow for much tighter tolerances which reduce oil bypassing and reduced ram scoring
- Air assisted lowering speeds up ram retraction
- Built in overload safety valve prevents damage to unit due to excessive load
- Comes with 2 extensions (75mm/3" + 45 mm1.75") and saddle adapter
- Units are tested to -13F(-25C) and +113F(+45C) as well as off center loading to ensure a long life under even the harshest conditions

Specifications:

25 Ton (1st Stage)

• Low Height: 185 MM (7.28")

• High Height: 282 MM (11.10")

• Lift - 97 MM (3.82")

10 Ton (2nd Stage)

• Low Height: 185 MM (7.28")

• High Height: 377 MM (14.84")

• Lift - 192 MM (7.56")

• Working Air Pressure 0.8 to 1.2 Mpa (116 to 174 psi)

• Net Weight: 53 kgs (117 lbs.)

• Shipping Weight: 58 kgs. (128 lbs.)

RELATED PRODUCTS



Model 545SD 30/15 Ton 2 Stage



Model 547SD 50/25 Ton 2 Stage



Model 548SD 60/40/20 Ton 3 Stage



Model 549SD 80/50 Ton 2 Stage