

# ALTO 4



## 3/4" - 1" FNPT COMPRESSED AIR TREATMENT UNITS...

Temperature  
+41°F to +122°F



Construction  
Body: Aluminum  
Polycarbonate  
bowl with metallic  
protection

Equipped with  
Manual drain



### ALTO 4 - 3/4" - 1" FILTER 25 MM

		A (inch)	B (inch)	NPT female thread	Flow rate (cfm at 87 psi ΔP=4psi)	Max operating pressure (psi)	Filtration (µm)	Part Numbers
		3.543	10.236	3/4" FNPT	176	174	25	<b>TF 204T</b>
		3.543	10.236	1" FNPT	229	174	25	<b>TF 205T</b>



### ALTO 4 - 3/4" - 1" REGULATOR

		A (inch)	B (inch)	NPT female thread	Flow rate (cfm at 87 psi ΔP=14psi)	Operating pressure (psi)	Part Numbers
		3.543	6.969	3/4" FNPT	176	Inlet: 217 Outlet: 7-145	<b>TR 204</b>
		3.543	6.969	1" FNPT	211	Inlet: 217 Outlet: 7-145	<b>TR 205</b>
Pressure gauge port size: G 1/4							

### ALTO 4 - 3/4" - 1" LUBRICATOR

		A (inch)	B (inch)	NPT female thread	Flow rate (cfm at 87 psi ΔP=7psi)	Max operating pressure (psi)	Part Numbers
		3.543	10.748	3/4" FNPT	254	174	<b>TL 204</b>
		3.543	10.748	1" FNPT	318	174	<b>TL 205</b>

### ALTO 4 - 3/4" - 1" FILTER-REGULATOR

		A (inch)	B (inch)	NPT female thread	Flow rate (Cfm at 87 psi ΔP=14psi)	Operating pressure (psi)	Filtration (µm)	Part Numbers
		3.543	14.567	3/4" FNPT	150	Inlet: 174 Outlet: 7-145	25	<b>TM 204</b>
		3.543	14.567	1" FNPT	194	Inlet: 174 Outlet: 7-145	25	<b>TM 205</b>
Pressure gauge thread size: G 1/4								