





Temperature +41°F to +122°F	Construction	Equipped with Manual drain
	Body: Aluminum Polycarbonate bowl with metallic protection	



### ALTO 3 - 1/2" FILTER-REGULATOR 280 PSI (GAUGE INCLUDED) WITH WALL BRACKET

		<b>A (inch)</b>	<b>B (inch)</b>	<b>NPT female thread</b>	<b>Flow rate (cfm at 87 psi ΔP=14psi)</b>	<b>Operating pressure (psi)</b>	<b>Filtration (μm)</b>	<b>Part Numbers</b>
		2.638	12.992	1/2" FNPT	105.96	Inlet: 290 Outlet: 7-181	40	<b>TM HPSM203</b>
Metallic vat without sight glass Equipped with a pressure gauge: 0 - 232 psi								

### ALTO 3 - 1/2" REGULATOR WITH GAUGE

		<b>A (inch)</b>	<b>B (inch)</b>	<b>NPT female thread</b>	<b>Flow rate (cfm at 87 psi ΔP=14psi)</b>	<b>Operating pressure (psi)</b>	<b>Part Numbers</b>	
		1.575	3.189	1/2" FNPT	141.20	Inlet: 217 Outlet: 7-145	<b>TR M203</b>	
Equipped with a pressure gauge: 0 - 145 psi								

### ALTO 3 - 1/2" HP REGULATOR WITH GAUGE

		<b>A (inch)</b>	<b>B (inch)</b>	<b>NPT female thread</b>	<b>Flow rate (cfm at 87 psi ΔP=14psi)</b>	<b>Operating pressure (psi)</b>	<b>Part Numbers</b>	
		2.795	6.299	1/2" FNPT	141.20	Inlet: 290 Outlet: 7-181	<b>TR HPM203</b>	
Equipped with a pressure gauge: 0 - 232 psi								