

## STEALTH unit



### Features & Benefits

- Inverse-Flow® Technology with 3½" filter depth
- Quick disconnect clamp ring design
- 1.0 micron final filtration
- Spin-on/spin-off element
- Equipped with brass petcock manual drain
- Rated for 60 SCFM
- Removes dirt & water
- Non-corrosive internal metal
- Pressure regulator/gauge standard
- Heavy duty metal bowl construction
- Cleaner compressed air with no water to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.5 % effective at water removal
- ½" BV-051 ball valve

### Specifications

- Replacement Element: 6950-1
- Max. Air Pressure: 150 PSIG
- Max. Operating Temp: 125° F
- Max. Flow: to 60 SCFM

### Applications

- Air Tools, Sand Blasting, Sanding Impacts, Buffing
- Ideal for Mechanical Section of Shop

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe



Removes: ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"**
  - STEALTH 6900B** No Regulator
  - STEALTH 6950B** Regulator w/ Gauge
  - STEALTH 6952B** Regulator w/ Gauge, (2) 1/4" Outlets
- 3/8"**
  - STEALTH 3050B** Regulator w/ Gauge
  - STEALTH 3052B** Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6950-1

Removes: ● ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"**
  - STEALTH 6910B** No Regulator
  - STEALTH 6960B** Regulator w/ Gauge
  - STEALTH 6962B** Regulator w/ Gauge, (2) 1/4" Outlets
- 3/8"**
  - STEALTH 3060B** Regulator w/ Gauge
  - STEALTH 3062B** Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6960-1

Removes: ● ●

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"**
  - STEALTH 7000B** Regulator w/ Gauge
  - STEALTH 7800B** No Regulator
- 1/2"**
  - STEALTH 1000B** Regulator w/ Gauge
  - STEALTH 1500B** Regulator w/ Gauge and manifold
- 3/8"**
  - STEALTH 7030B** Regulator w/ Gauge

Replacement Element: 3C-060

Removes: ● ● ●

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain  
2nd Stage: Brass Manual Petcock Drain



- 3/8"** **STEALTH 6060B** Regulator w/ Gauge

1st Stage Replacement Element: 6960-1  
2nd Stage Replacement Element: 3C-060

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key: ● Water ● Dirt ● Oil

CA PROPOSITION 65 WARNING  
**WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200

[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)

@RTiPBE

@rti\_pbe

