

Safety Data Sheet Lube-Tech Silicone Siping Lubricant Revision Date: 5/19/15

Prepared according to Global Harmonized System (GHS) standards

**SECTION 1** 

CHEMICAL PRODUCT IDENTIFICATION

Lubrication Technologies, Inc. 900 Mendelssohn Avenue North Golden Valley, MN 55427-4309 Tel: 763-545-0707

# Product Trade Name:

# Lube-Tech Silicone Siping Lubricant

CAS Number: Synonyms/Other: Part Number(s): Recommended Use: Restrictions on Use: Created Date: Preparation/Revision Date: Emergency Phone Number: SDS CODE: Mixture Silicone emulsion NA Siping Lubricant Not determined 5/19/2015 5/19/2015 1-800-424-9300 (CHEMTREC) 10300

# **SECTION 2**

#### HAZARD IDENTIFICATION

Appearance:	White liquid	
Odor:	No odor	
Classification:	Eye damage / irritation category 2	
	Acute Toxicity - oral category 4	
Target Organs:	Stomach and intestines, Eyes	
Pictogram(s):	$\wedge$	
	$\langle ! \rangle$	
	$\mathbf{\nabla}$	
Signal Word:	WARNING	
Hazard Statement:	H302 - Harmful if swallowed	
	H319 - Causes serious eye irritation	
Other Hazards:	Not determined.	
Prevention:	P264 - Wash hands thoroughly after handling	
	P270 - Do not eat, drink or smoke when using this product	
	P280 - Wear protective gloves/protective clothing/eye protection/face protection	
Response:	P330 - Rinse mouth	
·	P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel	
	unwell	
	P304+P341 - IF INHALED: If breathing is difficult, remove victim to fresh air and keep at	
	rest in a position comfortable for breathing	
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.	
	Remove contact lenses if present and easy to do – continue rinsing	
	P337+P313 - If eye irritation persists get medical advice/attention	
Storage Procedures:	None required.	
Disposal:	P501 - Dispose of contents and container in accordance with federal, state, and local	
-	regulations	
Other:	See section 11 for complete health hazard information.	



# **SECTION 3**

**SECTION 5** 

# **COMPOSITION OF INGREDIENTS**

Component	CAS Number	Percentage (by weight)
Octylphenoxypolyethoxyethanol	9036-19-5	1.0-3.0%
Polyalkleneoxide Modified Heptamethyltrisiloxane	67674-67-3	0.1-1.0%
1,3-Bis(hydroxymethyl)-5,5-dimethylimidazolidine-2,4-dione	6440-58-0	0.1-1.0%

The balance of components do not contribute to the overall classification of the fluid, according to the GHS Standard.

SECTION 4	FIRST AID MEASURES
Eye Contact:	Avoid direct contact. Wear chemical protective gloves, if necessary. Remove source of exposure or move person to fresh air. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice or attention.
Skin Contact:	Call a doctor if you feel unwell.
Inhalation:	Get medical advice or attention if you feel unwell or are concerned.
Ingestion:	Rinse mouth. Call a doctor if you feel unwell.
Other:	No additional information

FIRE FIGHTING MEASURES

Flash Point:	Not applicable.
Flammable limits:	Not applicable.
Extinguishing media:	Not applicable.
Special firefighting procedures	: General directions - product will not burn without driving water from material first. Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect personnel attempting to stop a leak. Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible (safely). Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage tank due to fire. Fire fighters must wear MSHA/NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.
Unusual fire & explosion hazards:	High temperatures may create heavy flammable vapors that may settle along ground level and low spots to create an invisible fire hazard.
Byproducts of combustion:	Fires involving this product may release oxides of carbon, nitrogen and sulfur; reactive hydrocarbons and irritating vapors.
Autoignition temperature:	Not determined.
Explosion data:	Not determined. Care should always be exercised in dust/mist areas.
Other:	Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

#### **SECTION 6**

UBE • TECH...

Accelerating Performance

#### ACCIDENTAL RELEASE MEASURES

Spill control procedures (land):	Immediately turn off or isolate any source of ignition (pilot lights, electrical equipment,
	flames, heaters, etc.). Evacuate area and ventilate. Personnel wearing proper protective
	equipment should contain spill immediately with inert materials (sand, earth, chemical
	spill pads of cotton) by forming dikes. Dikes should be placed to contain spill in a manner
	that will prevent material from entering sewers and waterways. Large spill, once
	contained, may be picked up using explosion proof, non-sparking vacuum pumps,
	shovels, or buckets, and disposed of in suitable containers for disposal. Clean up
	residue with water. If a large spill occurs notify appropriate authorities. In case of road
	spill or accident contact Chem-Trec (800-424-9300).

Spill control proceduresIf a large spill occurs notify appropriate authorities (normally the National Response(water):Center or Coast Guard at 800-424-8802).

**Waste disposal method:** Do not empty into drains. All disposals must comply with federal, state, and local regulations. The material, if spilled or discarded may be a regulated waste. Refer to state and local regulations. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. See Section 14.

Other: CAUTION - If spilled material is cleaned up using a regulated solvent, the resulting waste mixture will be regulated.

# SECTION 7 HANDLING AND STORAGE Handling procedures: Keep containers closed when not in use. Do not transfer to unmarked containers. Empty

	containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld, or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse. Handling temperatures should not exceed $60^{\circ}$ (140°F) to min imize danger of burns. Open containers carefully in a well ventilated area or use appropriate respiratory protection. Wash thoroughly after handling.
Storage procedures:	Store containers away from heat, sparks, open flame, or oxidizing materials. Extended storage at excessive temperatures may produce odorous and toxic fumes from product decomposition.

Additional information: No additional information.

#### **SECTION 8**

#### **EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure limits/standards for materials that can be formed when handling this product:


Component	CAS Number	OSHA PEL	ACGIH TLV
Octylphenoxypolyethoxyethanol	9036-19-5	-	-
Polyalkleneoxide Modified	67674-67-3	-	-
1,3-Bis(hydroxymethyl)-5,5-	6440-58-0	-	-

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

No biological limits allocated.

 Personal protection:
 Applicable mainly to persons in repeated contact situations such as packaging of product, service/maintenance, and cleanup/spill control personnel.

**Respiratory protection:** None required if ventilation is adequate. Otherwise a respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements must be followed. Where misting may occur, wear an MSHA/NIOSH approved (or equivalent) half-mask form dust/mist air purifying respirator.





Eye protection is strongly recommended. Wear safety glasses with side shields or Eye protection: vented/splash proof goggles (ANSI Z87.1 or approved equivalent). Hand protection: Impervious, chemically resistant gloves such as neoprene or nitrile rubber to avoid skin sensitization and absorption. Use of an apron and overboots of chemically impervious materials such as neoprene or Other protection: nitrile rubber is recommended based on level of activity and exposure. If handling hot material use insulated protective equipment. Launder soiled clothes. Properly dispose of contaminated leather articles and other materials which cannot be decontaminated. Local control measures: Use adequate ventilation when working with material in an enclosed area. Mechanical methods such as fume hoods or area fans may be used to reduce localized vapor/mist areas. If vapor or mist is generated when the material handled, adequate ventilation in accordance with good engineering practice must be provided to maintain concentrations below the specified exposure. Eyewash stations and showers should be available in areas where this material is used and stored. Other: Consumption of food and drink should be avoided in work areas where product is present. Always wash hands and face with soap and water before eating, drinking or

# PHYSICAL AND CHEMICAL PROPERTIES

smoking.

Appearance:	White liquid
Odor:	No odor
Odor threshold:	Not determined.
pH:	6.5 – 7.5.
Melting/Freezing point:	Not determined.
Initial boiling point:	Approximately 212年 (100℃)
Boiling range:	Not determined.
Flash point:	Not applicable.
Evaporation rate:	<1.
Flammability:	Non-flammable
Upper flammable limit:	Non-flammable
Lower flammable limit:	Non-flammable
Vapor pressure:	Similar to water.
Vapor density:	Not determined.
Relative density:	Not determined.
Solubility:	Miscible in water, negligible in most petroleum solvents.
Partition Coefficient:	Not determined.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Viscosity:	Not determined.
Other	Not applicable.

#### **SECTION 10**

**SECTION 9** 

#### **STABILITY AND REACTIVITY**

Reactivity Chemical stability: Hazardous polymerization: Conditions to avoid: Incompatibility with other materials:

Material is chemically stable at room temperatures and pressure. Will not occur. Avoid high temperatures and product contamination. Avoid contact with acids and strong oxidizing materials.



Safety Data Sheet Lube-Tech Silicone Siping Lubricant Revision Date: 5/19/15

**Decomposition products:** 

Smoke, carbon monoxide, carbon dioxide, and other aldehydes of incomplete combustion. Oxides of carbon, nitrogen, and sulfur; reactive hydrocarbons and irritating vapors. Not applicable.

Other:

**SECTION 11** 

# **TOXICOLOGICAL INFORMATION**

#### Acute toxicity (LD50) \*See note at the bottom of the section

,	
Oral:	300 - 2000 mg/kg
Dermal:	>5000 mg/kg
Inhalation:	>20.0 mg/l
Skin irritation:	Non-irritant
Eye irritation:	Causes serious eye irritation
Dermal sensitization:	Not expected to have a sensitizing effect.
Respiratory sensitization:	Not expected to have a sensitizing effect.
Aspiration Hazard:	Not applicable
Chronic Toxicity	
Mutagenicity:	Not suspected of causing genetic defects
Carcinogenicity:	Not suspected of causing cancer.
Reproductive toxicity:	Not expected to have adverse effects on reproduction.
STOT-single exposure:	Not expected to have adverse effects.
STOT-repeated exposure:	Not expected to have long term adverse effects.
Other:	*All data in this section is based off calculations from Part 3 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.

#### **SECTION 12**

#### **ECOLOGICAL INFORMATION**

Environmental toxicity			
Fish:	> 100 mg/l.		
Invertebrates:	> 100 mg/l.		
Aquatic plants:	> 100 mg/l.		
Microorganism:	> 100 mg/l.		
Persistence/Degradability:	This product is expected to be readily biodegradable.		
Bioaccumulation:	Not determined.		
Mobility in soil:	Not determined.		
Other:	All classifications are based on calculations in Part 4 of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) utilizing information from the constituent components.		

# SECTION 13 DISPOSAL CONSIDERATIONS

Waste disposal:	This product unadulterated by other materials can be classified as a non-hazardous waste. Depending on use, used product may be regulated. Dispose of in a licensed facility. Do not discharge product in to sewer system. Dispose of containers by crushing or puncturing, so as to prevent unauthorized use of used containers. Waste management should be in full compliance with federal, state, and local laws.
Other	The transportation, storage, treatment and disposal of RCRA waste material must be conducted in compliance with 40 CFR 262, 263, 264, 268 and 270. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate or otherwise inappropriate.



#### Safety Data Sheet Lube-Tech Silicone Siping Lubricant Revision Date: 5/19/15

#### **SECTION 14**

#### **TRANSPORT INFORMATION**

Land Transport (DOT): **Proper Shipping Name:** Land Transport (TDG): **Proper Shipping Name:** Sea Transport (IMDG): **Proper Shipping Name:** Air Transport (IATA): **Proper Shipping Name:** Other:

Not Regulated Not Regulated Not determined. Not applicable. Not determined. Not applicable. Not determined. Not applicable. Not applicable.

#### **SECTION 15**

#### **REGULATORY INFORMATION**

Federal Regulation			
Clean water act/oil:	No components of this product are listed.		
TSCA:	All components of this material are listed in the U.S. TSCA Inventory.		
Other TSCA:	Not applicable.		
SARA title III:	Section 302/304 extremely hazardous substances:		
	None.		
	Section 311, 312 hazard categorization:		
	Acute (immediate health effects):	YES	
	Chronic (delayed health effects):	NO	
	Fire (hazard):	NO	
	Reactivity (hazard):	NO	
	Pressure (sudden release hazard):	NO	
	Section 313 toxic chemicals:		
	No components present are at or greater than the de minimis (minimum reportable)		
	concentration requirements for reporting.		
CERCLA:	For stationary/moving sources – reportable quantity (due to):		
	Not regulated.		
State Regulations			
Right-to-know	Not determined.		
Other:	Environmental Response Compensation and Liability Act (CERCLA). However, release		
	may be reportable to the Nation Response Center under		
	1321(b)(3) and (5) - see head of Section 15. Failure to report may result in substantial		
	civil and criminal penalties.		
	Decommend contracting the local outherities in the event	t of any type of anill to determine	

Recommend contacting the local authorities in the event of any type of spill to determine local reporting requirements and also to aid in the cleanup.



SECTION 16	OTHER			
	NFPA 704	NPCA-HMIS	KEY	
HEALTH:	2	2	0 = Minimal	
FIRE:	0	0	1 = Slight	
REACTIVITY:	0	0	2 = Moderate	
SPECIFIC HAZARD:	None	N/A	3 = Serious	
PROTECTION INDEX:	N/A	В	4 = Severe	
Version:	I			

INFORMATION PROVIDED IN THIS SDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF THE AUTHORS' KNOWLEDGE. HOWEVER, THE AUTHOR'S MAKE NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. THE AUTHORS ASSUME NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments: None.