



AMERICANFORGE&FOUNDRY™

Ratcheting Torque Wrenches

- ✓ Tested at +/- 4% accuracy and includes Certificate of Calibration
- ✓ Conforms to the accuracy requirements of the American Standards Institute ASME B107.14-1194, BSEN 26789:1994, ISO 6789-1992, DIN 3122, and U.S. Government Specification GGG-W-00686C
- ✓ Perceptible jolt and audible click indicate desired torque setting has been reached
- ✓ Locking collar prevents accidental setting adjustment
- ✓ Pliable handle grip for superior comfort and oil resistance
- ✓ Rubber seal between the ratchet head and tube keeps lubrication in and contaminants out
- ✓ Includes protective blow mold case for easy storage



MODEL NUMBER	DRIVE SIZE	PRIMARY SCALE RANGE	SECONDARY SCALE RANGE	TOOTH COUNT	HEAD THICKNESS	HEAD WIDTH	OVERALL LENGTH	SHIP WEIGHT
41050	1/4"	40-250 in/lbs	5-28 Nm	24	0.44	1.14	13.75"	1.63 lbs
41051	3/8"	15/80 ft/lbs	20-108 Nm	24	0.58	1.44	15.25"	2.11 lbs
41052	1/2"	30/150 ft/lbs	40-203 Nm	24	0.64	1.85	21.00"	3.75 lbs
41053	1/2"	50-250 ft/lbs	67-339 Nm	24	0.76	1.85	25.50"	5.60 lbs
41054	3/4"	100-600 ft/lbs	135-813 Nm	24	1.04	2.85	43.00"	13.07 lbs
41055	1"	100-700 ft/lbs	135-949 Nm	24	1.04	2.85	48.00"	14.21 lbs